






Belt Power LLC
2197 Canton Rd, Suite 208
Marietta, GA 30066
800-886-BELT (2358)
www.beltpower.com

Fastener Selection Chart

	Fastener Type	Usage	Belt Thickness	PIW	Min Pulley Dia
	Bolt Solid Plate	Heavyweight – sift free splice with superior holding ability	3/16" – 1-3/16"	150 - 620	12" – 48"
	Bolt Hinged	Heavyweight – Ideal for belt applications subject to length adjustments.	1/4" – 5/8"	190 - 300	6" – 9"
	Rivet Hinged	Heavyweight – Very strong splice. Great alternative to vulcanized splice.	1/8" – 1"	330 – 2000	5" – 42"
	Alligator® Staple	Lightweight – Long service life, can be used in wide variety of applications.	1/16" – 1/4"	100 – 200	2" – 4"
	Clipper® Wire Hook	Lightweight – Most common used lace. Great for small pulley's.	1/64" – 25/64"	200	15/16" – 7"
	Alligator® Lacing	Lightweight – Can be installed without tools. Ideal for break down fixes.	1/64" – 1/2"	25 – 200	1" – 14"
	Plastic Rivet	Lightweight – Non-magnetic, quiet, and non-scratching splice.	1/64" – 1/8"	40 – 65	1-1/2" – 3"
	Plastic Spiral Lace	Lightweight – Ideal for small pulley's, non-metallic	1/16" – 3/16"	50	3/8" – 5/8"